




W = Width, D = Depth, H = Height



## DEFA PlugIn Relay 24V

DEFA PlugIn Relay 460856 is embedded in a suitable polyamide material. The relay contains of solid brass rail connectors to ensure long time durability.

DEFA AS is conforming to the requirements of both ISO 9001-2008, ISO 14001:2004 and OHSAS 18001:2007. In addition to this, our engine heaters and cables are conforming to the requirements of ISO/TS 16949:2002.

### Item number

DEFA no: 460856  
EAN Code: 7042284608568  
Weight: 59 gram

### Usage & Mounting

DEFA PlugIn Relay 460856 can be used with both control unit/timer and thermostat.

The relay is only to be connected to positive (X/Y) yellow cable from a DEFA timer. The relay get its negative signal through the PlugIn extension cable connected to the Bat -. A 1,5m earth wire is including.

Refer to enclosed product user and installation guide.

### Technical specifications

Voltage [V/Hz]	+24
Operating temperature [°C]	35
W/H/D [mm]	42-230 - 50/60
Net Weight [gram]	-40 /+60
IP rating	31/61/67
Insulation class	59
Certification- Safety	IP44
Certification - EMC	EN 50066:1992 EN 61058-1:2002;A2
Godkjenninger - EMC	EN 61058-1:2002; A2 EN 61000-3-2:2006 EN 61000-3-3:1995; A1; A2

[www.defa.com](http://www.defa.com)