




W = Width, D = Depth, H = Height

230V ~ 50Hz   



DEFA PlugIn Relay 24V

Place and fit the DEFA relay in the engine compartment according to the installation manual and suitable for the extension cables. Using the relay together with DEFA SmartStart™ makes it possible to control the engine heater separate from the interior heater.

DEFA AS is conforming to the requirements of both ISO 9001:2008, ISO 14001:2004 and OHSAS 18001:2007. In addition to this, our engine heaters and cables are conforming to the requirements of ISO/TS 16949:2002.

Item

DEFA number: 460863
Gross Weight: 140 gram

Part of

DEFA Relay is available as single units and together with the DEFA Futura timer.

Use & Mounting

Confer the enclosed product user and installation guide.

Technical specifications

Voltage [V/Hz]	230 +/- 5%
Operating temperature [°C]	-40 /+80
W/H/D [mm]	56/63/70
Net Weight [gram]	101
Bracket [gram]	20
IP rating	IP44
Insulation class	cl II
Certification- Safety	EN 60335-1, EN60 335-2-30 , NEK 554
Certification - EMC	EN 55014-1:2000; A1; A2 EN 61000-3-2:2000 EN 61000-3-3:1995; A1 EN 55014-2:1997; A1

www.defa.com

CE 041109 - DEFA PlugIn Relay 24V 863

